



Offset Blanket AIR-EXCEL **S 7400**

For use on high speed, sheet-fed presses. (Especially deep cut-down)

This blanket is designed for stable running on the press and an improvement in dot reproduction.

Characteristics

1. A great balance of dot reproduction and solid coverage has been achieved.
2. Excellent registration due to strict carcass manufacture control and face properties.
3. Reduced gauge loss achieved by careful selection of the fabric configuration and the compressibility.

Technical Data

Surface

Rubber Compound	For normal ink type
Finish	Ground & Buffed
Color	Blue

Construction

Compressible Layer	Open Cell
Thickness/Ply	2.50/4Ply

Application

Web Offset Presses
Sheet fed Presses

Physical Property of 1.95mm Type

Tensile Strength at Break	78kN/m
Elongation at Break	5.0%
Elongation at 500N/50mm	0.91%
Roughness <RA>	0.85 μ m
Hardness <Shore A>	81°
Compressibility at 0.2mm	1.73MPa
Paper Feeding Ratio	+0.54%

Physical Property of 1.68mm Type

Hardness <Shore A>	81°
--------------------	-----

kinyo

Kinyo UK Ltd., Kinyo House, Scala Court, Leathley Road,
Leeds LS10 1JD. Telephone: 0113 200 5680 Fax: 0113 200 5681
Email: sales@kinyo-uk.co.uk Web: www.kinyo-uk.co.uk